



Low Voltage Distribution Transformer -
Single Phase, 190/208/220/240 X
380/416/440/480 - 120/240V, 15kVA

By Acme Electric
Catalog # [TF279266S](#)

Low Voltage Distribution Transformer - Single Phase,
190/208/220/240 X 380/416/440/480 - 120/240V, 15kVA

Features

- Quiet operation with sound levels below NEMA standards
- Electrostatic shield for enhanced protection

Specifications

Buy American Compliant	Contact Manufacturer
CSA Standard	C22.2 No. 47
CE Compliant	CE Marked
UL Insulation Class	180°C
Nema Rating	NEMA 3R
UL Standard	UL 506
Buy America(n) Qualified	Contact Manufacturer

Configuration

Electrostatic Shield	Shielded
----------------------	----------

Current

Frequency Rating	50/60 Hz
kVA	15.0
Primary Voltage	190/208/220/240 X 380/416/440/480 V
Secondary Voltage	120/240 V
Primary Voltage	190 / 208 / 220 /240 X 380 / 416 / 440 / 480 V



Dimensions

Length	11.59 in
Width	14.12 in
Weight	170 lb.
Height	16.94 in
Dimensions	11.59 in x 14.12 in x 16.94 in

General

Winding Material	AL
Material type	ZFIN
Product Category	Dry Type Distribution Transformer
Construction	Encapsulated
UPC	047503420966
Mounting Type	Wall

Logistics

Carton Quantity	1
Pallet Quantity	6

Operational

Max Temperature Rise	115 Degrees Celsius
----------------------	---------------------

Product Assets

[Catalog \[English\]](#)