

Specifications

Photo is representative

Eaton CE15BNS3AB

Eaton XT IEC contactor, 10A, 110-120 Vac, 50-60 Hz, 1NO, 10A, Frame B, 45 mm, 50-60 Hz, 0.5 hp, Side, Three-pole, Non-reversing, No overload relay, Freedom, Contactor

General specifications

PRODUCT NAME	Eaton XT IEC contactor
CATALOG NUMBER	CE15BNS3AB
UPC	782113778075
PRODUCT LENGTH/DEPTH	3.25 in
PRODUCT HEIGHT	2.96 in
PRODUCT WIDTH	1.8 in
PRODUCT WEIGHT	0.9 lb
WARRANTY	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
COMPLIANCES	ISO 9000 DIN VDE 0600
CERTIFICATIONS	UL Listed IEC Rated CSA Certified
CATALOG NOTES	Fourth power pole position is used as the auxiliary contact and adds no additional width. No enclosure.
PRODUCT TYPE	Contactors

Product specifications

AMPERAGE RATING	10A
HP RATING - MAX	0.5 hp
NUMBER OF POLES	Three-pole
TYPE	Contacto
FREQUENCY RATING	50-60 Hz
FRAME SIZE	45 mm
COIL VOLTAGE	110-120 Vac, 50-60 Hz
CONTACT CONFIGURATION	1 NO
CONTINUOUS AMPERE RATING	10 A
RELAY	No overload relay
SERIES	Freedom
OPERATION	Non-reversing
MOUNTING METHOD	Side

Resources

CATALOGS	Motor Control and Protection, IEC Contactors and Starters, Volume 5, Tab 1
SPECIFICATIONS AND DATASHEETS	Eaton Specification Sheet - CE15BNS3AB

PROJECT NAME:

PROJECT NUMBER:

PREPARED BY:

DATE:



Eaton Corporation plc Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com

© 2026 Eaton. All Rights Reserved.

Follow us on social media to get the latest product and support information.

