

50 Amp, 125/250, 3Ø 250 Volts
and 3Ø 480 Volts AC



IP20
SUITABILITY



Plugs

Description	Cord Dia.	Catalog Number		
Nylon cover, thermoplastic polyester interior.	.830"-1.250" (21.08-31.75)	CS6365C	CS8365C	CS8165C

Note: See page C-60 for accessories.

Flanged Inlets

Description	Catalog Number		
Zinc plated steel casing, thermoset interior.	CS6375	CS8375	CS8175
Zinc plated steel casing, thermoset interior with lift cover.	CS6375M2	—	—
Gray Valox® housing and flange.	HBL6375S*	—	—

Note: *Type 3R (not shown).

IP20
SUITABILITY



Connector Bodies

Description	Cord Dia.	Catalog Number		
Nylon cover, thermoplastic polyester interior.	.830"-1.250" (21.08-31.75)	CS6364C	CS8364C	CS8164C
Insulgrip® Connector with conduit adapter. Capable of accepting metallic or non-metallic conduit fittings.	1/2" NPT Size 3/4" NPT Size 1" NPT Size	—	CS8364CA05 CS8364CA34 CS8364CA10	— — —

Note: See page C-60 for accessories.


Receptacles

Description	Catalog Number		
Black phenolic.	CS6369	CS8369	CS8169


Note: See page C-60 for accessories.



CS6365C



CS6375



CS6375M2




CS6364C



CS8364CA05



CS8364CA05
(Rear View)



CS6369

Valox® is a trademark of SABIC Innovative Plastics, acquired from General Electric Company.

Dimensions in Inches (mm)