




Classification Index

Classification of calipers

For outside	Digital Caliper  p. 1-1244 to 1252	Standard Calipers  p. 1-1253 to 1255	Long caliper  p. 1-1256 to 1257
	Long jaw caliper  p. 1-1258 to 1259	Both round port calipers  p. 1-1260	Round Hole Pitch Caliper  p. 1-1260 to 1262
For inside	Calipers for inside  p. 1-1263 to 1264	Others  p. 1-1265 to 1266	Dial shape  p. 1-1267

TRUSCO

TRUSCO

Stock
38,650
Items

Digital Caliper

Repairing
OKCalibration OK
Approx. 2 WeeksCom
Drawing

- Features • Adopted high speed model liquid crystal.
• Easy to see with the digital display. • Has a hold function.
- Use • For outer measurement, inner measurement, depth measurement, step difference measurement.
- Specs • Power Supply: Button Type Silver Oxide Battery (SR44) x 1 (sold separately)
- Origin • China

SPQ: 1 Piece

TRUSCO NAKAYAMA CORPORATION



TDN-150

Outer Side Jaws

Order Unit: 1 Piece

Order Code	Item No.	Price (per piece)	MSRP (per piece)	Measurement Range (mm)	Instrument Error (mm)	Minimum Display (mm)	Outer Side Jaws (mm)	Interior Jaws (mm)	Depth Bar	Weight (g)
489-0744	TDN-100	¥ 6,804	¥ 8,400	0 to 100	±0.03	0.01	40	16.5	Yes	150
489-0752	TDN-150	¥ 7,290	¥ 9,000	0 to 150	±0.03	0.01	40	16.5	Yes	170
489-0761	TDN-200	¥ 11,057	¥ 13,650	0 to 200	±0.03	0.01	50	19.5	Yes	210
489-0779	TDN-300	¥ 17,334	¥ 21,400	0 to 300	±0.04	0.01	60	21.5	Yes	280

Contact us: 0120-509-849 <http://www.orange-book.com/>

MITUTOYO

Mitutoyo

Stock
466
Items

"ABS Digimatic Caliper"

Repairing
OKCalibration OK
Approx. 2 Weeks

- Features • We adopted an electromagnetic induction type absolute encoder and improved environmental resistance performance.
• High contrast liquid crystal display reduces fatigue.
• Realized the operation of a firmly comfortable slider without unevenness.
• Built-in ABS scale eliminates origin alignment for each power on.
- Use • Step measurement, inner measurement, outer measurement, depth measurement, and the like.
- Specs • Power Supply: Button Type Silver Oxide Battery (SR44) x 1 (accessory)
- Origin • Japan

SPQ: 1 Piece

MITUTOYO CORPORATION



CD-15APX

Outer Side Jaws

Order Unit: 1 Piece

Order Code	Item No.	Price (per piece)	MSRP (per piece)	Manufacturer Code	Measurement Range (mm)	Instrument Error (mm)	Minimum Display (mm)	Outer Side Jaws (mm)	Interior Jaws (mm)	Depth Bar	Weight (g)
469-7430	CD-10APX	¥ 13,668	¥ 13,500	500-180-30	0 to 100	±0.02	0.01	40	16.5	Yes (round 1.9)	143
469-7456	CD-15APX	¥ 14,175	¥ 14,000	500-181-30	0 to 150	±0.02	0.01	40	16.5	Yes	168
469-7502	CD-20APX	¥ 18,225	¥ 18,000	500-182-30	0 to 200	±0.02	0.01	50	20.0	Yes	198

Contact us: 050-3786-3214 <http://www.mitutoyo.co.jp/>

MITUTOYO

Mitutoyo

Stock
466
Items

"ABS Digimatic Caliper" (with data output terminal)

Repairing
OKCalibration OK
Approx. 2 Weeks

- Features • High contrast liquid crystal display reduces fatigue.
- Use • Step measurement, inner measurement, outer measurement, depth measurement, and the like.
- Specs • Power supply: Button type silver oxide battery (SR44) x 1 (accessory)
• With measurement data output terminal
- Origin • Japan

SPQ: 1 Piece

MITUTOYO CORPORATION



CD-15AX

Outer Side Jaws

Order Unit: 1 Piece

Order Code	Item No.	Price (per piece)	MSRP (per piece)	Manufacturer Code	Measurement Range (mm)	Instrument Error (mm)	Minimum Display (mm)	Outer Side Jaws (mm)	Interior Jaws (mm)	Depth Bar	Weight (g)
469-7448	CD-10AX	¥ 15,188	¥ 15,000	500-150-30	0 to 100	±0.02	0.01	40	16.5	Yes (round 1.9)	143
469-7464	CD-15AX	¥ 15,693	¥ 15,500	500-151-30	0 to 150	±0.02	0.01	40	16.5	Yes	168
469-7472	CD-15AXR	¥ 15,693	¥ 15,500	500-158-30	0 to 150	±0.02	0.01	40	16.5	Yes (round 1.9)	168
469-7511	CD-20AX	¥ 19,743	¥ 19,500	500-152-30	0 to 200	±0.02	0.01	50	20.0	Yes	198
105-2071	CD-30C	¥ 36,957	¥ 36,500	500-153	0 to 300	±0.03	0.01	64	21.8	Yes	350

Contact us: 050-3786-3214 <http://www.mitutoyo.co.jp/>