



XS Series 1-Pole Tumbler Switch Cover With Device - 20A

By Killark
Catalog # [XS-1C](#)

XS Series - Aluminum 1-Pole Tumbler Switch Cover With Device - 20A



Features

- Front lever rotary operated switch assemblies.
- Standard provisions for padlocking in either “ON” or “OFF” position.
- The lever is connected to a threaded stainless steel shaft which passes through the cover.

Application

Used where making, breaking, or changing connections in an electric circuit is required.

Specifications

EU RoHS Indicator	Contact Manufacturer
CSA File Number	LR11712
Hazardous Rating(s)	• Class I, Divisions 1 & 2, Groups C, D • Class I, Zones 1 & 2, Groups IIB, IIA • Class II, Divisions 1 & 2, Groups E, F, G • Class III, Divisions 1 & 2
UL File Number	E53360
Buy America(n) Qualified	Contact Manufacturer

Conductor

Number Of Poles	1
-----------------	---

Configuration

Back Box Type	SWB
---------------	-----

Current

Amperage Rating	20 A
Frequency Rating	50/60 Hz

Dimensions

Depth	4-1/4 in
Length	3.5 in
Gross Weight with Packaging	1.098
Width	7.875 in
Weight	1.098 lb.
Height	3.25 in
Dimensions	3.5 in x 7.875 in x 3.25 in

General

Series	XS Series
Color	Gray
Type	Aluminum Tumbler Switch Cover
Material	Aluminum, Copper Free (less than 4/10 of 1%)
UPC	783936925004

Operational

Action	SPST
Actuator	Lever

Product Assets

[Catalog \[English\]](#)
[Installation Manual \[French, English\]](#)